



# SUPERSEAL All-In-One Subfloor Product Specification Sheet

Phone: 1-800-571-1877  
Fax: 604-576-2458

www.superseal.ca  
info@superseal.ca

September 01, 2010 - present

Moisture will always find a way through cracks or voids and into your home. The moisture can damage your flooring, attract mold and mildew and decrease the indoor air quality. SUPERSEAL All-In-One Subfloor blocks moisture, is resistant to alkalines and will not rot or degrade. All-In-One protects your homes value while providing you with a dry and comfortable home.

Part #	Roll Sizes
SA84166	3'3" x 50'10" - 166 ft <sup>2</sup> - (1.0 x 15m)
SA84332	6'7" x 50'10" - 332 ft <sup>2</sup> - (2.0 x 15m)

Properties	Values
Material - Dimpled Sheet	High-Denisty Polyethylene (HDPE)
Color - Dimpled Sheet	Black
Thickness - Dimpled Sheet	0.5 mm (20mil)
Area Weight (approx)	500 g/m <sup>2</sup>
Dimple Height	3mm (1/8")
Dimple Spacing (approx)	2500 per m <sup>2</sup>
Air Gap Between Dimples	7.9 l/m <sup>2</sup>
Compressive Strength	350 kN/m <sup>2</sup> (7800 psf)
Service Temperature Range	-40° C to +80° C

**SUPERSEAL All-In-One Subfloor is made from up to 80% recycled plastic and is;**

- **IMPERVIOUS** to root penetration and rot proof.
- **RESISTANT to;** fungus and bacterial attack, concentrated acetic acid, alcoholic beverages, ammonia aqueous, diesel fuel, dishwashing soap, fruit juices, hydrofluoric acid up to 20%, Hydrofluoric acid up to 35%, laundry detergents, methanol, milk, motor oil, concentrated potassium hydroxide, silicone oil, soap solution - aqueous, concentrated sodium hydroxide, sulfuric acid up to 40%, vegetable oils & fats, cold water, hot water, saltwater.
- **CONDITIONALLY RESISTANT to;** acetone, benzene, ozone, gasoline (petrol) and toluene.

## Areas of Application / Benefits

- For use wherever carpet or laminate is installed to control moisture and to increase floor temperature
- Residential and commercial applications such as basements and wood substrates 90% lighter and 10x faster than plywood
- Makes floors more comfortable to walk on
- Compatible with heated floor systems
- No need for plywood or nails when installing carpet or laminate  
Warmer and softer floors

**SUPERSEAL** warranties this product for a period of 20 years and is resistant to a wide range of chemicals, resistant to fungus and bacterial attack, impervious to root penetration and rot proof. In the event this product fails to meet these requirements, the said amount of material shall supplied free of charge. There are no warranties beyond this expressed as stated above. **SUPERSEAL** assumes no responsibility for any other losses or damages, labour, materials, punitive, incidental or consequential or otherwise. Proof of purchase must be provided at time of claim.